



CETRA 2018

5th International Conference on Road and Rail Infrastructure
17–19 May 2018, Zadar, Croatia

Road and Rail Infrastructure V

Stjepan Lakušić – EDITOR



Organizer
University of Zagreb
Faculty of Civil Engineering
Department of Transportation



CETRA²⁰¹⁸

5th International Conference on Road and Rail Infrastructure

17–19 May 2018, Zadar, Croatia

TITLE

Road and Rail Infrastructure V, Proceedings of the Conference CETRA 2018

EDITED BY

Stjepan Lakušić

ISSN

1848-9850

ISBN

978-953-8168-25-3

DOI

10.5592/CO/CETRA.2018

PUBLISHED BY

Department of Transportation

Faculty of Civil Engineering

University of Zagreb

Kačićeva 26, 10000 Zagreb, Croatia

DESIGN, LAYOUT & COVER PAGE

minimum d.o.o.

Marko Uremović · Matej Korlaet

PRINTED IN ZAGREB, CROATIA BY

“Tiskara Zelina”, May 2018

COPIES

500

Zagreb, May 2018.

Although all care was taken to ensure the integrity and quality of the publication and the information herein, no responsibility is assumed by the publisher, the editor and authors for any damages to property or persons as a result of operation or use of this publication or use the information's, instructions or ideas contained in the material herein.

The papers published in the Proceedings express the opinion of the authors, who also are responsible for their content. Reproduction or transmission of full papers is allowed only with written permission of the Publisher. Short parts may be reproduced only with proper quotation of the source.

Proceedings of the
5th International Conference on Road and Rail Infrastructures – CETRA 2018
17–19 May 2018, Zadar, Croatia

Road and Rail Infrastructure V

EDITOR

Stjepan Lakušić
Department of Transportation
Faculty of Civil Engineering
University of Zagreb
Zagreb, Croatia

ORGANISATION

CHAIRMEN

Prof. Stjepan Lakušić, University of Zagreb, Faculty of Civil Engineering
Prof. emer. Željko Korlaet, University of Zagreb, Faculty of Civil Engineering

ORGANIZING COMMITTEE

Prof. Stjepan Lakušić
Prof. emer. Željko Korlaet
Prof. Vesna Dragčević
Prof. Tatjana Rukavina
Assist. Prof. Ivica Stančerić
Assist. Prof. Maja Ahac
Assist. Prof. Saša Ahac
Assist. Prof. Ivo Haladin
Assist. Prof. Josipa Domitrović
Tamara Džambas
Viktorija Grgić
Šime Bezina
Katarina Vranešić
Željko Stepan

Prof. Rudolf Eger
Prof. Kenneth Gavin
Prof. Janusz Madejski
Prof. Nencho Nenov
Prof. Andrei Petriaev
Prof. Otto Plašek
Assist. Prof. Andreas Schoebel
Prof. Adam Szeląg
Brendan Halleman

INTERNATIONAL ACADEMIC SCIENTIFIC COMMITTEE

Stjepan Lakušić, University of Zagreb, president
Borna Abramović, University of Zagreb
Maja Ahac, University of Zagreb
Saša Ahac, University of Zagreb
Darko Babić, University of Zagreb
Danijela Barić, University of Zagreb
Davor Brčić, University of Zagreb
Domagoj Damjanović, University of Zagreb
Sanja Dimter, J. J. Strossmayer University of Osijek
Aleksandra Deluka Tibljaš, University of Rijeka
Josipa Domitrović, University of Zagreb
Vesna Dragčević, University of Zagreb
Rudolf Eger, RheinMain Univ. of App. Sciences, Wiesbaden
Adelino Ferreira, University of Coimbra
Makoto Fujii, Kanazawa University
Laszlo Gaspar, Széchenyi István University in Győr
Kenneth Gavin, Delft University of Technology
Nenad Gucunski, Rutgers University
Ivo Haladin, University of Zagreb
Staša Jovanović, University of Novi Sad
Lajos Kisgyörgy, Budapest Univ. of Tech. and Economics

Anastasia Konon, St. Petersburg State Transport Univ.
Željko Korlaet, University of Zagreb
Meho Saša Kovačević, University of Zagreb
Zoran Krakutovski, Ss. Cyril and Methodius Univ. in Skopje
Dirk Lauwers, Ghent University
Janusz Madejski, Silesian University of Technology
Goran Mladenović, University of Belgrade
Tomislav Josip Mlinarić, University of Zagreb
Nencho Nenov, University of Transport in Sofia
Mladen Nikšić, University of Zagreb
Andrei Petriaev, St. Petersburg State Transport University
Otto Plašek, Brno University of Technology
Mauricio Pradena, University of Concepcion
Carmen Racanel, Tech. Univ. of Civil Eng. Bucharest
Tatjana Rukavina, University of Zagreb
Andreas Schoebel, Vienna University of Technology
Ivica Stančerić, University of Zagreb
Adam Szeląg, Warsaw University of Technology
Marjan Tušar, National Institute of Chemistry, Ljubljana
Audrius Vaitkus, Vilnius Gediminas Technical University
Andrei Zaitsev, Russian University of transport, Moscow



IMPACTS OF AUTONOMOUS VEHICLES ON THE URBAN FUNDAMENTAL DIAGRAM

Qiong Lu, Tamás Tettamanti

Budapest University of Technology and Economics, Faculty of Transportation Engineering and Vehicle Engineering, Department of Control for Transportation and Vehicle Systems, Hungary

Abstract

In recent years, self-driving cars are being introduced to streets, which generated significant attention and discussion. The widespread adoption of autonomous vehicles (AV) brings changes in several fields. One of the most exciting changes is presented by the effect that driverless cars bring to the well-known traditional traffic model, the Macroscopic Fundamental Diagram (MFD). This is a key issue as MFD is a basic model for strategic traffic planning and also for real-time traffic control. In this paper therefore the impacts of autonomous vehicles that are relevant to the urban MFD are investigated through traffic simulation. The paper seeks the answer to a basic question, i.e. how the different percentage of autonomous vehicles among traditional vehicles and the autonomous driving levels influence the urban MFD. A detailed simulation study was carried with SUMO (microscopic traffic simulation software) in an artificial grid network.

Keywords: autonomous vehicles, percentage, autonomous driving levels, fundamental diagram, urban traffic, SUMO

1 Introduction

In our days and in the near future connected and automated vehicles transform our traditional transportation systems (SAE International, 2014; Szigetzi et al., 2017). Therefore, the impact of autonomous transport must be properly investigated as it directly influences the traffic dynamics, the applicable control, as well as the methodologies for traffic network analysis and planning [1, 2].

An autonomous vehicle (AV) by definition is a vehicle that is capable of sensing its environment and navigating without human input. Based on the amount of driver intervention and attentiveness required, the autonomous driving is classified into six different levels by the Society of Automotive Engineers (SAE) international. The SAE international delivered a harmonised classification system for Automated Driving Systems (ADS), specifically SAE J3016 Taxonomy and Definitions for Terms Related to On-Road Motor Vehicle Automated Driving Systems (see Table 1) [3].

Experience with the availability and deployment of previous vehicle technologies can be used to forecast the AVs implementation. The penetration of driverless cars depends on both availability and user acceptance of the technology. Based on some widely accepted basic principles [4], six scenarios with different penetration in each autonomous driving level are studied in this paper.

Table 1 The levels of automation defined in SAE J3016 [3]

Level 0 No automation	The full-time performance by the human driver of all aspects of the dynamic driving task, even when enhanced by warning or intervention systems
Level 1 Driver Assistance	The driving mode-specific execution by a driver assistance system of either steering or acceleration/deceleration using information about the driving environment and with the expectation that the human driver performs all remaining aspects of the dynamic driving task.
Level 2 Partial Automation	The driving mode-specific execution by one or more driver assistance systems of both steering and acceleration/deceleration using information about the driving environment and with the expectation that the human driver performs all remaining aspects of the dynamic driving task.
Level 3 Conditional Automation	The driving mode-specific performance by an automated driving system of all aspects of the dynamic driving task with the expectation that the human drivers respond appropriately to a request to intervene.
Level 4 High Automation	The driving mode-specific performance by an automated driving system of all aspects of the dynamic driving task, even if a human driver does not respond appropriately to a request to intervene.
Level 5 Full Automation	The full-time performance by an automated driving system of all aspects of the dynamic driving task under all roadway and environmental conditions that can be managed by a human driver.

The Macroscopic Fundamental Diagram (MFD) of traffic flow is practically a set of diagrams that gives relationships among the traffic flow Q (vehicles/h), the traffic density ρ (vehicles/km) and the space mean speed V (km/h) [5]. The MFD can be used to define the capacity and thus the service level of a road system. Moreover, the MFD describes traffic dynamics when applying inflow regulation or speed limits. Fundamental diagram consists of three different (two dimensional) graphs: flow-density, speed-flow, and speed-density. All the graphs are related by the fundamental equation:

$$Q(\rho) = \rho \cdot V(\rho) \quad (1)$$

The fundamental diagram can be derived by plotting of field data points and using appropriate curve fitting to the scatter plots. MFD can also be applied for urban or metropolitan areas as proposed by [6]. The concept of urban MFD has been widely investigated during the past decades, e.g. [7-10]. The aim of this work is to study the potential impact of autonomous vehicles on the classical urban MFD.

2 Method

In this research, there are two main parameters to investigate in relationship with the fundamental diagram, i.e. the impact of penetration (percentage of AVs in the whole traffic flow) and autonomous driving level. The work has been carried out with SUMO microscopic traffic simulation software by using different car types and percentages. The simulations were run in a grid network considering each group of these new parameters. The traffic volume of the links as well as the throughput of the whole network were measured in the simulator virtually. All measures of the MFD can be obtained from SUMO's edgeData which represents macroscopic link-level measurement practically. The results were evaluated in order to understand the evolution of the different scenarios and reveal the relationships between network capacity, percentage of autonomous car as well as autonomous driving level. Regarding the MFD, network-level and link-level fundamental diagram can be distinguished, both by using Eq. (1). The first one models the throughput of the traffic network per hour:

$$Q_N(\rho_a) \quad (2)$$

Where Q_N is the number of vehicles that pass the network. ρ_a is the average density of the network, and it simply equals to the known total number of vehicles in the network divided by the total link kilometres of the road network, i.e.

$$\rho_a = \frac{\sum_{i=1}^n \rho_i l_i}{\sum_{i=1}^n l_i} \quad (3)$$

Where l_i is the length of link i , n is the number of links [5,10]. The second approach interprets the MFD of one single road link of the network, i.e.

$$Q_i(\rho_i) = \rho_i \cdot V_i(\rho_i) \quad (4)$$

Where Q_i is the flow, ρ_i means the density, $V_i(\rho_i)$ defines the mean velocity, and Q_i is the flow on link i . In our work, fundamental diagrams were modelled as polynomials. Thus, the points of the simulation results were approximated with cubic polynomial curve fitting (the fitting curve was constrained to cross the original):

$$Q(\rho) = a \cdot \rho^3 + b \cdot \rho^2 + c \cdot \rho \quad (5)$$

Where a , b , c are polynomial coefficients.

3 Simulation study and evaluation

In order to analyse the effect of automated and autonomous technology a detailed simulation study was carried with SUMO microscopic traffic simulator.

3.1 Network setup and scenarios

As shown in Fig. 1, a grid traffic network was constructed, designed to represent common situation on the urban road network. The applied network was an 8x8 grid, i.e. 64 intersections in the network. The length between adjacent node was 500 meters. The network edges were bidirectional road links with single lanes. A traditional “time gap based” traffic signal method was applied (built-in tool of SUMO [11]). This control scheme switches to the next phase after detecting a sufficient time gap between successive vehicles in order to achieve a better distribution of green-time among phases dynamically [12].




Figure 1 Grid test traffic network

As the aim of this work is to investigate potential impacts of driverless cars on road network performance, a straightforward approach to autonomous vehicles fleet penetration has been taken. This is based upon some basic principles that are widely accepted:

- at low market penetration, technical capability is limited (for example, to driver assistance which mean low autonomous driving level);
- as market penetration increases, consumer confidence also augments and better use of connected and automated technology prevail [4].

Fig. 2 shows an example projection for the increasing technical capability of AVs overtime. Technological change is usually marked by early adopters prior to full saturation. The scenarios for AV deployment should reflect this. Measurements in one link and in the whole network were realized. The modelled scenarios are summarised in Table 2.




Figure 2 Future states of availability and user acceptance [4]

Table 2 The scenarios used in this simulation

Scenario nr.	Scenarios	Ratio of traditional cars	AV penetration composition				
			Level 1	Level 2	Level 3	Level 4	Level 5
1	Base	100 %	0 %	0 %	0 %	0 %	0 %
2	25 % penetration	75 %	15 %	5 %	5 %	0 %	0 %
3	50 % penetration	50 %	25 %	10 %	10 %	5 %	0 %
4	75 % penetration	25 %	25 %	20 %	15 %	10 %	5 %
5	100 % penetration	0 %	15 %	20 %	20 %	25 %	20 %
6	Upper bound	0 %	0 %	0 %	0 %	0 %	100 %

3.2 Autonomous vehicle modelling methodology

Default SUMO parameters have been modified in order to model a plausible future for AVs. In this paper, the default car following model was applied (Krauss Model). The parameter selection is related to longitudinal movement, acceleration, deceleration and gap acceptance. These behaviours are formalised as parameters in the car-following model of SUMO. The implemented model follows the idea as that let vehicles drive as fast as possibly while maintaining perfect safety (always being able to avoid a collision if the leader starts braking within leader and follower maximum acceleration bounds). The following list shows the editable parameters of the Krauss Model:

- Mingap: the offset to the leading vehicle when standing in a jam (in m).
- Accel: The acceleration ability of vehicles of this type (in m/s^2).
- Decel: The deceleration ability of vehicles of this type (in m/s^2).
- Emergency Decel: The maximum deceleration ability of vehicles of this type in case of emergency (in m/s^2).
- Sigma: The driver imperfection (between 0 and 1).
- Tau: The driver's desired (minimum) time headway (reaction time) (in s).

For level 0 the default values were taken for all parameters. But the emergency deceleration was set to $8 m/s^2$. This value is based on the study of [13]. For other autonomous driving levels, the deceleration and the emergency deceleration remained the same, considering the safety. For the level 2 and level 5, the mingap, acceleration, time headways were taken from [4]. For level 1, the values of these items were set as the average value of level 0 and level 2. For the level 3 and level 4, the values of these items were changed linearly between level 2 and level 5. The driver imperfection for level 5 and level 4 was set to 0, because these levels do not need human driver's intervention. It was assumed to be 0.4, 0.3 and 0.2 for level 1, level 2 and level 3, respectively. The parameters for all levels are tabulated to Table 3.

Table 3 Variables in SUMO car-following model

Capacity level	Mingap (m)	Accel (m/s^2)	Decal (m/s^2)	Emergency Decel (m/s^2)	Sigma (driver imperfection)	Tau (s)
Level 0	2.5	2.6	4.5	8	0.5	1.0
Level 1	2	3.05	4.5	8	0.4	0.95
Level 2	1.5	3.5	4.5	8	0.3	0.9
Level 3	1.25	3.6	4.5	8	0.2	0.8
Level 4	0.75	3.7	4.5	8	0	0.7
Level 5	0.5	3.8	4.5	8	0	0.6

3.3 Simulation results

The main simulation results are provided by Figs 3-4. and Table 4. From the results for the whole network, one can see that from scenario 1 to scenario 6 the capacity of the whole network and the critical density vary. Scenario 6 has the largest critical density straightforwardly. The same tendency can be found in whole network for critical density and capacity that going up in the beginning, then decreasing, roaring up at the end. From the results for one single link, one can see that the capacities for scenario 1, 2, 3 and 4 are similar and relatively smaller, and the capacities for scenario 5 and 6 are bigger and have an increasing trend. The same change can be found on the critical densities. Fig. 4. shows the coefficients of the fitting curves which are fitted with quadratic polynomials. From the changes of the coefficients, one can see, the goodness of fitting is relatively high which means the total variation of the coefficients can be explained by the quadratic polynomials well.




Figure 3 Simulation results for the whole network and a single link

Table 4 Network overall fitting result

$$Q = a \cdot \rho^3 + b \cdot \rho^2 + c \cdot \rho$$

Scenario	Network					Single link				
	a	b	c	ρ_{crit}	Q_{max}	a	b	c	ρ_{crit}	Q_{max}
1	1.7978	-239.19	5502.3	14	35112	3.63e-04	-0.3372	38.5766	62	1182
2	4.2538	-318.17	6253.9	13	36906	4.71e-04	-0.3331	37.1062	67	1132
3	3.5108	-299.51	6392.7	14	40434	7.33e-04	-0.3696	38.1478	64	1120
4	6.2310	-421.07	7640.7	13	41887	7.39e-04	-0.3561	37.2340	63	1118
5	3.0208	-261.08	5813.0	15	38648	7.66e-04	-0.3759	41.5738	69	1331
6	0.3600	-153.71	5097.1	18	44059	2.20e-04	-0.2543	38.9403	92	1601




Figure 4 The variations of the fitted polynomial coefficients (network level) together with the regression curves

4 Conclusion

The effect of automated and autonomous vehicles to the urban MFD have been analysed through microscopic traffic simulation. A thorough simulation study was fulfilled in a grid traffic network. The results justified some regularity in the change of the urban MFD (network and link level as well) along with the autonomous technology evolution. The results are also important from the point of view of practical traffic engineering as the fundamental diagram is a common modelling approach when planning or analysing a road network. Therefore, one should take these changes into consideration in the future.

Acknowledgement

The research work was supported by the Hungarian Government and co-financed by the European Social Fund (EFOP-3.6.3-VEKOP-16-2017-00001: Talent Management in Autonomous Vehicle Control Technologies) and by the János Bolyai Research Scholarship of the Hungarian Academy of Sciences.

References

- [1] Kisgyorgy, L., Vasvari, G.: Analysis and observation of road network topology, 19th International Conference of Hong Kong Society for Transportation Studies, Hong Kong, December 2014,
- [2] Szigeti, S., Csiszar, C., Foldes, D.: Information Management of Demand-Responsive Mobility Service Based on Autonomous Vehicles, *Procedia ENGINEERING* 187: pp. 483-491. 2017.
- [3] S. O.-R. A. V. S. Committee et al., "Taxonomy and definitions for terms related to on-road motor vehicle automated driving systems," SAE Standard J3016, pp. 01–16, 2014.
- [4] A. Ltd, "Research on the impacts of connected and autonomous vehicles (cavs) on traffic flow research on the impacts of connected and autonomous vehicles (cavs) on traffic flow," tech. rep., Department for Transport, 2016.
- [5] Williams, J.C., Mahmassani, H.S., Iani, S., Herman, R.: "Urban traffic network flow models," *Transportation Research Record*, vol. 1112, pp. 78–88, 1987.
- [6] Godfrey, J.: "The mechanism of a road network," *Traffic Engineering & Control*, vol. 8, no. 8, 1969.
- [7] Mahmassani, H., Williams, J.C., Herman, R.: "Performance of urban traffic networks," in *Proceedings of the 10th International Symposium on Transportation and Traffic Theory*, pp. 1–20, Elsevier Amsterdam, The Netherlands, 1987.
- [8] Daganzo, C.F.: "Urban gridlock: Macroscopic modeling and mitigation approaches," *Transportation Research Part B: Methodological*, vol. 41, no. 1, pp. 49–62, 2007.
- [9] Keyvan-Ekbatani, M., Papageorgiou, M., Papamichail, I.: "Perimeter traffic control via remote feedback gating," *Procedia-Social and Behavioral Sciences*, vol. 111, pp. 645–653, 2014.
- [10] Csikos, A., Tettamanti, T., Varga, I.: "Macroscopic modeling and control of emission in urban road traffic networks," *Transport*, vol. 30, no. 2, pp. 152–161, 2015.
- [11] "Simulation/traffic lights," http://sumo.dlr.de/wiki/Simulation/Traffic_Lights, 14 March 2018.
- [12] Krajzewicz, D., Erdmann, J., Behrisch, M., L. Bieker, L.: "Recent development and applications of SUMO – Simulation of Urban MObility," *International Journal On Advances in Systems and Measurements*, vol. 5, pp. 128–138, December 2012.
- [13] Kudarauskas, N.: "Analysis of emergency braking of a vehicle," *Transport*, vol. 22, no. 3, pp. 154–159, 2007.