



**CETRA** 2018

5<sup>th</sup> International Conference on Road and Rail Infrastructure  
17–19 May 2018, Zadar, Croatia

# Road and Rail Infrastructure V

Stjepan Lakušić – EDITOR



Organizer  
University of Zagreb  
Faculty of Civil Engineering  
Department of Transportation



**CETRA**<sup>2018</sup>

**5<sup>th</sup> International Conference on Road and Rail Infrastructure**

17–19 May 2018, Zadar, Croatia

TITLE

Road and Rail Infrastructure V, Proceedings of the Conference CETRA 2018

EDITED BY

Stjepan Lakušić

ISSN

1848-9850

ISBN

978-953-8168-25-3

DOI

10.5592/CO/CETRA.2018

PUBLISHED BY

Department of Transportation

Faculty of Civil Engineering

University of Zagreb

Kačićeva 26, 10000 Zagreb, Croatia

DESIGN, LAYOUT & COVER PAGE

minimum d.o.o.

Marko Uremović · Matej Korlaet

PRINTED IN ZAGREB, CROATIA BY

“Tiskara Zelina”, May 2018

COPIES

500

Zagreb, May 2018.

Although all care was taken to ensure the integrity and quality of the publication and the information herein, no responsibility is assumed by the publisher, the editor and authors for any damages to property or persons as a result of operation or use of this publication or use the information's, instructions or ideas contained in the material herein.

The papers published in the Proceedings express the opinion of the authors, who also are responsible for their content. Reproduction or transmission of full papers is allowed only with written permission of the Publisher. Short parts may be reproduced only with proper quotation of the source.

Proceedings of the  
5<sup>th</sup> International Conference on Road and Rail Infrastructures – CETRA 2018  
17–19 May 2018, Zadar, Croatia

# Road and Rail Infrastructure V

**EDITOR**

Stjepan Lakušić  
Department of Transportation  
Faculty of Civil Engineering  
University of Zagreb  
Zagreb, Croatia

## ORGANISATION

### CHAIRMEN

Prof. Stjepan Lakušić, University of Zagreb, Faculty of Civil Engineering  
Prof. emer. Željko Korlaet, University of Zagreb, Faculty of Civil Engineering

### ORGANIZING COMMITTEE


Prof. Stjepan Lakušić  
Prof. emer. Željko Korlaet  
Prof. Vesna Dragčević  
Prof. Tatjana Rukavina  
Assist. Prof. Ivica Stančerić  
Assist. Prof. Maja Ahac  
Assist. Prof. Saša Ahac  
Assist. Prof. Ivo Haladin  
Assist. Prof. Josipa Domitrović  
Tamara Džambas  
Viktorija Grgić  
Šime Bezina  
Katarina Vranešić  
Željko Stepan

Prof. Rudolf Eger  
Prof. Kenneth Gavin  
Prof. Janusz Madejski  
Prof. Nencho Nenov  
Prof. Andrei Petriaev  
Prof. Otto Plašek  
Assist. Prof. Andreas Schoebel  
Prof. Adam Szeląg  
Brendan Halleman

### INTERNATIONAL ACADEMIC SCIENTIFIC COMMITTEE

Stjepan Lakušić, University of Zagreb, president  
Borna Abramović, University of Zagreb  
Maja Ahac, University of Zagreb  
Saša Ahac, University of Zagreb  
Darko Babić, University of Zagreb  
Danijela Barić, University of Zagreb  
Davor Brčić, University of Zagreb  
Domagoj Damjanović, University of Zagreb  
Sanja Dimter, J. J. Strossmayer University of Osijek  
Aleksandra Deluka Tibljaš, University of Rijeka  
Josipa Domitrović, University of Zagreb  
Vesna Dragčević, University of Zagreb  
Rudolf Eger, RheinMain Univ. of App. Sciences, Wiesbaden  
Adelino Ferreira, University of Coimbra  
Makoto Fujii, Kanazawa University  
Laszlo Gaspar, Széchenyi István University in Győr  
Kenneth Gavin, Delft University of Technology  
Nenad Gucunski, Rutgers University  
Ivo Haladin, University of Zagreb  
Staša Jovanović, University of Novi Sad  
Lajos Kisgyörgy, Budapest Univ. of Tech. and Economics

Anastasia Konon, St. Petersburg State Transport Univ.  
Željko Korlaet, University of Zagreb  
Meho Saša Kovačević, University of Zagreb  
Zoran Krakutovski, Ss. Cyril and Methodius Univ. in Skopje  
Dirk Lauwers, Ghent University  
Janusz Madejski, Silesian University of Technology  
Goran Mladenović, University of Belgrade  
Tomislav Josip Mlinarić, University of Zagreb  
Nencho Nenov, University of Transport in Sofia  
Mladen Nikšić, University of Zagreb  
Andrei Petriaev, St. Petersburg State Transport University  
Otto Plašek, Brno University of Technology  
Mauricio Pradena, University of Concepcion  
Carmen Racanel, Tech. Univ. of Civil Eng. Bucharest  
Tatjana Rukavina, University of Zagreb  
Andreas Schoebel, Vienna University of Technology  
Ivica Stančerić, University of Zagreb  
Adam Szeląg, Warsaw University of Technology  
Marjan Tušar, National Institute of Chemistry, Ljubljana  
Audrius Vaitkus, Vilnius Gediminas Technical University  
Andrei Zaitsev, Russian University of transport, Moscow



## FROM MANUAL INSPECTION TO PERMANENT MONITORING OF TURNOUTS

Petra Antonia Wilfling

*Graz University of Technology, Institute of Railway Engineering and Transport Economy, Austria*

### Abstract

The condition of turnouts is still evaluated manually by the inspection staff. Generally, the railway infrastructure manager blocks the track section during the inspection time. This leads to a decreasing availability. Moreover, employees are working in danger areas. Nonetheless, all of those inspection tasks have further challenges. The evaluated condition depends on the subjective assessment of the staff and the inspections carried out are not completely reproducible and do not allow a prognosis of maintenance demands yet. Finally, the manual inspections are executed without the load-impact of rail vehicles. These facts show the need for a shift from a manual inspection to an automatic self-inspection of turnouts towards a smart infrastructure. The measurement systems for open track and turnouts as also for the fix-installed, wayside sensors of eight companies were thus chosen and analysed and then compared with the inspection tasks of the Swiss Federal Railways to identify the feasibility of this automatic self-inspection.

*Keywords: turnout, infrastructure, inspection, maintenance demands, prognoses*

### 1 Introduction

Turnouts are essential assets for railway operation. The capacity of the rail network and possible speed are influenced by the condition and construction type of turnouts [1]. Within a track section, turnouts represent an area of discontinuity of the rather homogenous track structure. The track geometry is changed due to the different specifications of the main construction parts of turnouts. Furthermore, the different length of sleepers also influences track peculiarity by changing the stiffness along the turnout [2].

Variable construction parts of turnouts must endure high dynamic forces during the passage of a rail vehicle [2]. The crossing nose is one of the parts that is most strongly influenced. To prevent the thin crossing nose from barging of the rail wheel, it is constructed with a lower surface level. Unfortunately, this difference has negative effects, because the wheel has to drop at the force transmission point. This vertical movement generates high dynamic forces and an impact on the crossing nose, [3, 4]. The check rails are also located within the crossing panel to guarantee a safe passage of the rail vehicle. Furthermore, they ensure that the wheel will not damage the crossing nose by creating a fix defined flange way. However, this also creates additional forces [3].

The switch panel is not subjected to such an influence of extraordinary forces. As opposed to the crossing nose, the running edge of this area is similarly constructed as in the open track. An almost equal wear mechanism thus occurs in this area, [3]. However, the contact area between the wheel and rail changes with the beginning of the switching toes and different force transmissions appear. In order to achieve a secure fit of the switch rails at the stock rails, they are specially ground for each other. As a result, the switch toes are very thin and

the profile is weakened. The high forces during the passage lead to plastic deformations of the switch toes [5]. Within the closure panel, virtually the same conditions are found as in the open track. Different dynamic forces are only generated if a rail vehicle negotiates the diverging track of turnouts. These are the results of the missing transition curve [6]. These different dynamic forces lead to a rapid deterioration of the main components and further to a decreasing quality of the turnout [6]. To guarantee a safe passage of the rail vehicle and also a comfortable ride for the passenger, it is essential to carry out specific maintenance tasks [5]. The actual condition of each component and of the turnout overall must be known.

## 2 Inspection strategy

Currently, the inspection is executed manually. The infrastructure manager generally blocks the track section during the inspection time. This leads to a decreased availability. However, there are also differences between the national strategies and implementation methods.

In Switzerland, the inspection tasks are done during the railway operation within the intervals between train passages. The staff has to protect themselves while carrying out inspection tasks. Only if they cannot guarantee their own safety while performing different measurements or due to the alignment, an additional person, known as the “safety guard”, is present to guarantee the safety of the inspection team. Despite this, those track sections where speeds greater than 160 km/h are permitted must be blocked in Switzerland too, because of the high speeds mean approaching rail vehicles cannot always be recognised in good time [7].

Inspection and gauge measurement tasks are done manually at fix defined time intervals. These intervals depend on the type of the turnout and also the permitted speed on the track section, but the inspection is still time-based, [8]. Moreover, specific aspects of the current inspection procedure should also be mentioned. The evaluation of the actual condition is done by the inspection staff. They thus describe each component in addition to the whole turnout. Due to this procedure, the estimation of deterioration and the actual condition are dependent on the subjective assessment made by the staff. Furthermore, all the measurements are done without the inclusion of the rail vehicle load-impact.

The scatter of the manually collected measurement data and also the description of the actual condition make prediction of the maintenance demands and the optimal timing scarcely possible. A detection of the deterioration rate at an early state and reproducible measurement data could be done with an automatic machine based inspection of a turnout. Furthermore, entering the hazard zone for the inspection tasks would no longer be necessary and this would naturally mean that any risks could be considerably reduced.

## 3 Analysis of automatic inspection

All inspection tasks are listed in the technical regulations of Swiss Federal Railways. To analyse the possibility of an automatic and machine-based inspection, it was first necessary to classify the inspection tasks in the context of the different turnout components. After this step, all of the 91 inspection tasks for turnouts were compared with the available technologies for open track and turnouts and also with the fix installed wayside sensors.

The analysis itself was executed on the basis of a simple comparison of each single inspection task with the acquisition option of the technologies and systems. A categorisation into five groups of the facility for an automatic inspection was thus performed. Possible inspection tasks were separated from those which are not possible. Furthermore, those tasks, which can only be carried out by automatic inspection under specific preconditions or with the assistance of another technology, were assigned to a separate category. Within this classification, several inspection tasks are mentioned, which in theory it is possible to carry out through the use of a number of different technologies, even when this is not yet being done. Allowance was made for these by the introduction of another inspection task category. The same pro-

cedure was made for those tasks, which are theoretically not possible. Eight international companies were chosen for this analysis:

- DMA Srl, Torino (Italy)
- Eurailscout Inspection & Analysis B.V., Amersfoort (Netherlands)
- Fugro RailData, Utrecht (Netherlands)
- MER MEC Sp.A., Monopoli (Italy)
- Plasser & Theurer – Export von Bahnbaumaschinen GmbH, Vienna (Austria)
- Protran Technology LLC, New Jersey (USA)
- Terra Vermessungen AG, Zurich (Switzerland)
- VAE GmbH und voestalpine SIGNALING Zeltweg GmbH, Zeltweg (Austria).

Each one of these companies is a distributor of its own different systems or technologies each with its own specific modes of operation. This represents a good array of potential technologies for the analysis. The assessment thus also comprises the technologies of one company which are specially constructed for a wayside application on turnouts. Other systems can be used for onboard-monitoring systems on passenger or freight trains. In addition, self-propelled diagnostic vehicles were included in this investigation.

The condition of turnouts can be determined by use of a variety of cameras or other optical systems. Moreover, some of the companies mentioned offer systems with special cameras, which are able to record the surrounding environment in almost 360°. Furthermore, laser technologies are able to scan the rail profiles. The mode of operation differs from system to system. The possibility of using different determining methods and different fields of application promises relatively good results for an automatic and permanent inspection of turnouts.

## 4 Results

The research showed the differences between the modes of operation in the technologies considered. It was found that from 21 % to 62 % of the 91 different inspection tasks can be performed automatically by the system or with a combination of technologies from each company considered (Fig. 1).




Figure 1 Percentage of automation of the respective technologies

Nevertheless, the majority of the inspection tasks is only possible in theory or under certain preconditions or even not possible in theory. As a result, an accumulation of the category groups is necessary. Those inspection tasks, which can only be carried out under certain preconditions, were assigned to the category of the possible inspection tasks. Through this allocation, the classification was reduced to implementations that are possible or not possible. On this basis every single system or chosen combination from each company was now able to perform from 46 % to 67 % of all the necessary inspection tasks (Fig. 2).

This is a quite high possible automation level. At this point it shall be pointed out that a target of 100 % should be reached, however, otherwise the remaining inspection tasks will still need to be carried out manually. This would have a negative effect and the advantages of an automatic and permanent inspection would be put at risk.




Figure 2 Percentage of automation in the various technologies (summarised)

Due to the different modes of operation of fix-installed wayside applications, these provide a very satisfactory support of a different determination type to the other inspection and measurement systems. By combining the wayside technologies with the onboard-monitoring systems or independent inspection and measurement systems from the remaining other seven companies, the percentage of each combination could be increased by 30 %. With this result, at least 96 % of all inspection tasks could be performed automatically and with no need to deploy any inspection staff in the danger area (Fig. 3).

Only 4 % cannot be executed with this combination, but these inspection tasks may be possible using another combination. An examination of a combination of all the technologies has not yet been done, because it would appear to be very unlikely that an infrastructure manager would be able to acquire all of these systems.

At this point, an important aspect of the percentages must be mentioned. The feasibility of each system should not be seen as an indicator of concordant inspection tasks between the different technologies. The percentage acquired is only the sum of the 91 inspection tasks, which it is possible to perform with the technology, of this single company. This percentage provides no information accordant inspection tasks using resources provided by different companies. It is thus possible that two equal percentages may not have matching inspection tasks.






Figure 3 Percentage of automation of the respective technologies combined with wayside application (“WSA”)

## 5 Conclusion

This study points to the opportunity for an automatic and permanent inspection of a turnout. A combination of wayside sensors with onboard inspection and measurement technologies enables a very high automation possibility of 96 %. A combined system, as shown here, would make it possible to collect reproducible inspection data and ensure potential time series, for predicting the optimal maintenance tasks and the time in which they should be done. This would have a positive influence on the lifetime of a turnout. The feasibility of an inspection during the intervals between trains in running operation is not currently possible. The independent system must change the travel direction for inspections of the through and diverging track. Further advanced research is thus necessary for the achievement of integration into the railway operation. Nonetheless, this present study shows the possibility for a chance of the manual strategy and the opportunity for an automatic and permanent inspection of turnouts.

## References

- [1] Lichtberger, B.: Handbuch Gleis, DW Media Group GmbH, Hamburg 2010.
- [2] Zarembski, A.M.: Improving inspection of turnouts, Railway Track & Structures Volume 109 Issue 11 (2019), S. 24-27.
- [3] Zoll, A.: Einsatz neuer Werkstoffe für die Weiche — Erfahrungen aus der Sicht des Anwenders, Materials Testing Volume 53 Issue 4 (2011), S. 193-197.
- [4] Nicklisch, D. et al.: Messung und Bewertung der Überlaufgeometrie starrer Herzstücke, Der Eisenbahningenieur Ausgabe 009 (2013), S. 18-23.
- [5] Geiliené, I. et al.: Research on the lifetime of the switch and assumptions of increasing it, TRANSPORT Volume 23 Issue 2 (2008), S. 150-155.
- [6] Licciardello, R.V. et al.: Some experience on the dynamics of turnouts due to passing trains, 8th World Congress on Railway Research (WCRR) 2008, Seoul, Korea.
- [7] R RTE 20100: Sicherheit bei Arbeiten im Gleisbereich, Verband öffentlicher Verkehr, Bern Juni 2017.
- [8] R RTE 22066: Einbau, Kontrollen und Unterhalt der Weichen, Verband öffentlicher Verkehr, Bern April 2015.

